

**POTVRDA O TIPNOM ODOBRENJU**
TYPE APPROVAL CERTIFICATE

Br /No	03-001297/030962
--------	------------------

Potvrđuje se da je ovaj proizvod, u skladu s Pravilima za klasifikaciju brodova, Dio 1. - Opći propisi, Odjeljak 3. - Tipno odobrenje proizvoda, odobren za ugradnju na brodove i postrojenja pod nadzorom Hrvatskog registra brodova.

This is to certify that this product, on the basis of the Rules for the classification of ships, Part 1 - General requirements, Chapter 3 - Type approval of products, is approved for use on board ships and installations under supervision of the Croatian Register of Shipping.

TIP I OPIS PROIZVODA:*TYPE AND DESCRIPTION OF PRODUCT:***BRODSKI INSTRUMENTACIJSKI, KOMUNIKACIJSKI I KONTROLNI KABEL BEZHALOGENI I VATROOTPORNI***SHIPBOARD INSTRUMENTATION, COMMUNICATION AND CONTROL CABLE HALOGEN FREE AND FIRE RESISTANT***RFA-FRHF / RFA-FRHF(i) 150/250 V (300 V)****PROIZVOĐAČ:***MANUFACTURER:***HELKAMA BICA Oy***Lakimiehenkatu 4**FIN-20780 Kaarina***FINLAND****PROIZVOD UDOVOLJAVA SLIJEDEĆIM PRAVILIMA/PROPISIMA:***THE PRODUCT MEETS FOLLOWING RULES/REGULATIONS:***HRB PRAVILA ZA KLASIFIKACIJU BRODOVA: DIO 12 - ELEKTRIČNA OPREMA**
CRS RULES FOR THE CLASSIFICATION OF SHIPS: PART 12 - ELECTRICAL EQUIPMENT

Helkama specification: HBKQ 9 spec.57 and 58

Technical specification:

Design standard:

IEC 60092-376 (2nd ed. 2003-05),

Cables for control and instrumentation circuits 150/250 V (300 V)

Other standards:

- testing:

IEC 60092-350 (3rd Ed. 2008-02), General constructions and testing requirements

- insulation:

IEC 60092-351 (3rd ed. 2004-04), Insulating materials for shipboard power cables

- sheathing:

IEC 60092-359 (1.2nd ed. 1999-08)

Sheathing materials for shipboard power and telecommunication cables

DETALJI O PROIZVODU I UVJETIMA CERTIFIKACIJE DANI SU NA POLEDINI.*FURTHER DETAILS OF THE PRODUCT AND CONDITIONS FOR CERTIFICATION ARE GIVEN OVERLEAF.***ODOBRENJE VRIJEDI DO:****2016-02-10***APPROVAL IS VALID UNTIL:***Mjesto i datum:**

Split, 2012-02-10

*Place and date:***M.P.***(Seal)*

Goran Begović, dipl.ing.

NAPOMENA: Ova potvrda nije valjana ako se proizvod ili način njegove proizvodnje promijenio u odnosu na tipno ispitani proizvod. Proizvođač treba obavijestiti Hrvatski registar brodova o bilo kojoj izmjeni na proizvodu kako bi ishodio valjanu potvrdu.

NOTE: This certificate is not valid for equipment, the design or manufacture of which has been varied or modified from the specimen tested. The manufacturer should notify Croatian Register of Shipping of any modification or changes to the product in order to obtain a valid certificate.

PODROBNIJI OPIS PROIZVODA:*DETAILED PRODUCT DESCRIPTION:*

Flame retardant, fire resistant, halogen free, crosslinked polyethylene (XLPE) insulated, individual / collective (tape) screened, polyolefine sheathed, instrumentation, communication and control cable 150/250 V (300 V)

RFA-FRHF collectively screened
RFA-FRHF(i) individually and collectively screened

RFA-FRHF

<u>No of pairs</u>	<u>Cross sectional area (mm²)</u>
1, 1x4 ⁽¹⁾ , 2, 4, 7, 8, 10, 12, 14, 16, 19, 24, 32 and 37	0.5, 0.75 & 1.5
1x3	0.5, 0.75 & 1.5

⁽¹⁾Quadruple**RFA-FRHF(i)**

<u>No of pairs</u>	<u>Cross sectional area (mm²)</u>
1, 1x4 ⁽¹⁾ , 2, 4, 7, 8, 10, 12, 14, 16, 19, 24, 32 and 37	0.5, 0.75 & 1.5
1x3	0.5, 0.75 & 1.5

⁽¹⁾Quadruple**PODRUČJE PRIMJENE / POSEBNI GRANIČNI UVJETI:***APPLICATION / LIMITATIONS:*

Fiksna ugradnja na pomorskim brodovima, odobalnim objektima i industriji.

Fixed installation in marine, offshore and industrial use.

DOKUMENTACIJA ZA TIPNO ODOBRENJE:*TYPE APPROVAL DOCUMENTATION:*

Helkama Application on RFA-FRHF/RFA-FRHF(i) 150/250 V (300 V)	2012-01-27
Helkama RFA-FRHF 250 V Cable Data Sheet Specification HBKQ 9. Spec 57 incl. App 2	2010-08-03
Helkama RFA-FRHF(i) 250 V Cable Data Sheet Specification HBKQ 9. Spec 58 incl. App 2	2010-08-03

Izveštaj o ispitivanju/ test report:

Dim/RFA-FRHF 250 V TT; MC_1/ RFA-FRHF 250 V TT; Hotset/ RFA-FRHF 250 V TT; MC_S/ RFA-FRHF 250 V TT;
Hotdef/ RFA-FRHF 250 V TT; HST/ RFA-FRHF 250 V TT

IEC 60332-1-2/ RFA-FRHF 250 V TT; IEC 60332-3-22/ RFA-FRHF 250 V TT; IEC 60754-1/ RFA-FRHF 250 V TT;
IEC 60754-2/ RFA-FRHF 250 V TT

OZNAČAVANJE PROIZVODA:*MARKING OF PRODUCT:*

LOT ##### RFA-FRHF <number of conductors> x <size>mm² 250 V + 90°C
IEC 60092-376, 60331-21, 60332-3-22 HELKAMA "month-year" and "length marking"

LOT ##### RFA-FRHF(i) <number of conductors> x <size> mm² 250 V + 90°C
IEC 60092-376, 60331-21, 60332-3-22 HELKAMA "month-year" and "length marking"

UVJETI ZA CERTIFIKACIJU:*CONDITIONS FOR CERTIFICATION:*

NON

Raščlana

12.05.01

Zamjenjuje potvrdu

-